



The most precise and flexible all-rounder instrument for professional applications-easy to handle and robust for measurement of Temperature/Humidity, flow, co2 and air pressure

- **Parameters measured**

Integrated sensor for air pressure, exchangeable sensors for highly precise measurements of temperature, relative humidity and air flow

- **Measurement technology**

Various - thus exchangeable sensors

- **Product highlights**

Precise and flexible all-rounder handheld instrument, easy to handle and robust, sensor connection with automatic recognition, saves measuring campaigns, allows all climate data to be calculated and archived, evaluation software SmartGraph3 included

- **Interfaces**

USB (Cable and SmartGraph3 software included)

- **Article number**

5900.00

"All-rounder" in the handheld measurement technology segment. A universal measuring device for professionals with the inclusion of exchangeable SDI Sensors. Highly precise measurements of temperature and relative humidity. Integrated air pressure sensor, online/offline data recording. Equipped with test certificate, can be calibrated. Scope of delivery includes transport case.

# Technical Data

All-in-One Handheld Device XA1000



Beschreibung	Wert
--------------	------

General	
---------	--

Dimensions	170 x 62 x 34 mm
Weight	Approx. 205 g

Storage conditions	
--------------------	--

Permissible ambient temperature	-20...60 °C
Operating rel. humidity	< 90 % r.h. non - condensing

Operating conditions	
----------------------	--

Operating rel. humidity	< 90 % r.h. (20 g/m <sup>3</sup> ) non - condensing
Admissible height above absolute altitude	4000 m

Power supply	
--------------	--

Power supply	4 Alkaline LR6 AA 1.5 V/USB 5 V
Active power consumption	Approx. 400 mW
Battery life passive	Approx. 1 year
Battery life active	min. 24 hours
Sensor power supply	5.5 V ± 10 % DC, max. 200 mA

Data storage	
--------------	--

Integrated data storage	up to 200 gauges taking approx. 1 mill. values
-------------------------	--

Interface	
-----------	--

USB	Cable and SmartGraph3 software included
-----	---

Display	
---------	--

Definition of measured values	2 decimal places
Control	Touch screen, capacitive
Technology	TFT, resolution 240 x 320, 65 k colours, very good contrast due to Piezoresistive technology
Surface, toughened glass	Degree of hardness: 7, scratch - resistant

Integrated air pressure sensor	
--------------------------------	--

Measurement range	800...1100 mbar
Accuracy at 25°C, 1013.25mbar	0.5 mbar
Long-term stability	typ. 1 mbar/year
Measurement resolution	0.024 mbar
Measuring principle	Piezoresistive
Compatibility	Sensor/probe: all SDI/digital sensors (temperature, humidity, SDI airflow, air pressure integrated)

Others	
--------	--

<p>Calculated measurement categories for external temperature/humidity sensors</p>	<p>Mathematical: MIN/MAX/AVG/HOLD                  Temperature (°C/°F)                  Rel. humidity (% RH)                  Rel. humidity of ice (% RH)                  Water vapour density (absolute humidity) g/m<sup>3</sup>                  Dew point temperature °C/°F                  Frost point temperature °C/°F                  Mixing ratio at saturation (100%) g/kg                  Volume fraction of water vapour /mass fraction of water vapour (%)                  Wet-bulb temperature °C/°F                  Ice-bulb temperature °C/°F                  Specific Enthalpy (mass of air) kJ/kg                  Saturation vapour pressure above ice/water (hPa)                  Vapour particle pressure (hPa)                  Air density kg/m<sup>3</sup></p>
<p>Calculated measurement categories for external airflow sensors</p>	<p>Operating air flow volume - various units: (m<sup>3</sup>/s) (m<sup>3</sup>/h) (l/min);                  Standard air flow volume: DIN 1343 (°C, 1013.25hPa), ISO 2533 (15°C, 1013.25hPa), DIN 1945 (20°C, 1013.25hPa);                  Various units: (m<sup>3</sup>/s), (m<sup>3</sup>/min), (m<sup>3</sup>/h), (l/min)</p>